

DECLARATION OF PERFORMANCE
Under the CPR EU 305/2011
No. 2022-006 SA43

1. Unique identification code of the product-type:

ONDUTISS® AIR METAL 440, ONDUTISS® AIR METAL 440 T, ONDUTISS® AIR METAL 440 TT

2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Underlays for discontinuous roofing

3. Name, registered trade name or registered trademark and contact address of the manufacturer as required under Article 11(5):

ONDULINE SA
24 QUAI GALLIENI
92 150 SURESNES – FRANCE
www.onduline.com

4. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not Applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 3

6a. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 13859-1: 2014

Notified Body (NB) : **No 1213, SKZ - Testing GmbH**

7. Declared performances

Characteristics before aging :	Unit	Performance	Tolerance	Harmonized technical specification
Reaction on fire	Class	E	-	EN13859-1 :2014
Resistance to water penetration	Class	W1	-	
Tensile strength along MD /CD	[N/50mm]	295/205	± 15%	
Elongation along MD / CD	[%]	40/70	± 15%	
Tear resistance along MD /CD	[N]	160/210	± 15%	
Flexibility at low temperature	-	Pass	-	
Dimensional stability	-	Pass	-	
Dangerous substances	-	NPD	-	
Resistance to artificial aging :				
Resistance to water penetration	Class	W1	-	EN13859-1 :2014
Tensile strength along MD /CD	[N/50mm]	240/160	± 15%	

8. Appropriate Technical Documentation and/or Specific Technical documentation: **NO**

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Christophe ROHART
R&D Director

Suresnes, 13/02/2023 Ver.2





1213

ONDULINE SA
24, QUAI GALLIENI – 92 150 SURESNES – FRANCE

www.onduline.com

22

DOP N° 2022-006 SA43

EN 13859-1 :2014

**ONDUTISS® AIR METAL 440, ONDUTISS® AIR METAL 440 T,
ONDUTISS® AIR METAL 440 TT**

Underlays for discontinuous roofing

Characteristics before aging :

Reaction to fire (class):	E	
Watertightness (class):	W1	
Tensile strength along MD / CD (N/50mm):	295 / 205	± 15%
Elongation along MD / CD (%):	40 / 70	± 15%
Tear resistance along MD / CD (N):	160 / 210	± 15%
Flexibility at low temperature :	Pass	
Dimensional stability :	Pass	
Dangerous Substances :	NPD	

Durability :

Watertightness (class):	W1	
Tensile strength along MD / CD (N/50mm):	240 / 160	± 15%